

轮片特点

轮面材料:	人造胶	轮芯材料:	高强度聚丙烯
轴 承:	单滚珠	胎面硬度:	75A±3
建议温度:	-15°C~60°C	运行速度:	3.2km/h

注意: 超出建议温度范围或超出建议速度使用, 可能会缩短产品使用寿命甚至损坏产品。

- ✓ 高级人造胶材质, 注塑粘合成型
- ✓ 环保静音, 有效保护地面
- ✓ 配塑料护盖, 防缠绕






运行省力	■ ■ ■ □ □	一般
磨损寿命	■ ■ ■ □ □	一般
静音效果	■ ■ ■ ■ ■	优秀
地面保护	■ ■ ■ ■ ■	优秀

支架特点




- ✓ 踩踏省力, 解刹方便
- ✓ 304不锈钢冲压成型, 防锈防腐
- ✓ 防尘圈有效保护油脂润滑, 避免灰尘等杂质进入
- ✓ 抛光处理, 光亮美观
- ✓ 精密304不锈钢轴承, 防锈、转动灵活
- ✓ 镀锌处理, 盐雾测试满足48小时以上

外形尺寸 (mm)	 载重	 轮径	 轮宽	 全高	 偏心距 F	 旋转半径 r	 旋转半径 R
3"	80 kg	75	32	108	34	71.5	108.5
4"	90 kg	100	32	135	32	82	108.5
5"	95 kg	125	32	160	32	94.5	112.5




[中文简体]


安装尺寸



平底活动/刹车底板



平底固定底板



丝杆

产品代码					
产品图片					
轮径	平板万向	平板定向	平板刹车	丝杆万向	丝杆刹车
3"	20D01-1375	20D03-1375	20D02-1375	20D13-1375	20D14-1375
4"	20D07-1377	20D09-1377	20D08-1377	20D15-1377	20D16-1377
5"	20D10-1378	20D12-1378	20D11-1378	20D17-1378	20D18-1378

产品特征



电解抛光, 美观简洁

凹凸设计防尘盖, 防尘, 防缠绕

防尘圈保护, 有效防尘, 保护油脂。

