

轮片特点

轮面材料:	高强度聚丙烯	轮芯材料:	高强度聚丙烯
轴 承:	特尔灵	胎面硬度:	75D±3
建议温度:	-25°C~80°C	运行速度:	4km/h

注意: 超出建议温度范围或超出建议速度使用, 可能会缩短产品使用寿命甚至损坏产品。

- ✔ 特尔灵轴承, 防水、防锈
- ✔ 聚丙烯材质, 整体注塑成型, 轻便, 经济耐用
- ⚠ 耐磨性能较低
- ⚠ 运行有一定噪音












运行省力	■■■■■	优秀
磨损寿命	■■■□□	一般
静音效果	■■□□□	可接受
地面保护	■■□□□	可接受



支架特点


- ✔ ON/OFF双踏板结构, 踩踏方便, 制动效果出色
- ✔ 304不锈钢冲压, 焊接成型, 防锈防腐
- ✔ 防尘圈有效保护油脂润滑, 避免灰尘等杂质进入
- ✔ 抛光处理, 光亮美观

外形尺寸 (mm)	 载重	 轮径	 轮宽	 全高	 偏心距 F	 旋转半径 r	 旋转半径 R
4"	180 kg	100	422	145	34	84	141
5"	210 kg	125	45	165	38	100.5	141
6"	260 kg	150	45	190	44	119	141
8"	280 kg	200	45	240	54	154	154




[中文简体]

安装尺寸



产品代码

产品图片



轮径

平板万向

平板定向

平板刹车

4"

35D01-1419

35D03-1419

35D02-1419

5"

35D04-1420

35D06-1420

35D05-1420

6"

35D07-1421

35D09-1421

35D08-1421

8"

35D10-1421

35D12-1421

35D11-1421

产品特征

AB刹车，制动退刹便捷。刹车装置螺杆链接，方便维修更换。



油嘴注油，保养维护便捷。防尘圈保护，有效防尘，保护油脂润。



可根据使用场合，灵活选择特尔灵，不锈钢或者不锈钢轴承

